

# HYDROSEAL HF

Acrylic Universal Waterproof Coating

## PRODUCT DATA SHEET

HydroSeal HF is a specially formulated co-polymer emulsion. A coating that is UV stable, with medium elasticity increasing its flexibility. It is colour fast and designed to be 100% waterproof at full curing.

Coverage:	<ul style="list-style-type: none"><li>• 20 Liter : 16 -20 m<sup>2</sup> at 1-1.5mm</li><li>• 5 Liter: 4 – 5 m<sup>2</sup> at 1-1.5mm</li></ul>
Drying Time:	<ul style="list-style-type: none"><li>• Touch Dry: 1 – 2 Hours at ± 25°C</li><li>• Full Curing: 7 Days at ± 25°C</li></ul>
Cleaning:	<ul style="list-style-type: none"><li>• Clean water</li></ul>
Regulatory Data:	
Flashpoint:	<ul style="list-style-type: none"><li>• &gt;90°C</li></ul>
Product Weight:	<ul style="list-style-type: none"><li>• SP 1.2</li></ul>
VOC:	<ul style="list-style-type: none"><li>• Low VOC's &lt;1 %</li></ul>
Characteristics:	<ul style="list-style-type: none"><li>• Non-Flammable</li><li>• WaterProof</li><li>• Medium Elasticity – increased flexibility</li><li>• UV Stable</li><li>• Excellent adhesion properties – Adhesion promoted</li></ul>
Safety Precautions & Reactivity:	
Inhalation:	<ul style="list-style-type: none"><li>• No specific hazards associated with this product</li><li>• No specific health warnings noted</li></ul>
Ingestion:	<ul style="list-style-type: none"><li>• No harmful effects expected in amount likely to be indigested by accident - consult a Physician immediately</li></ul>
Skin Contact:	<ul style="list-style-type: none"><li>• Prolonged contact may cause dryness of the skin</li></ul>
Eye Contact:	<ul style="list-style-type: none"><li>• May cause temporary eye irritation</li></ul>
Health Warnings:	<ul style="list-style-type: none"><li>• This product has low toxicity. Only large volumes may have adverse impact on human health</li></ul>
Ecological Information:	<ul style="list-style-type: none"><li>• Eco Toxicity: 98 % Eco Friendly</li></ul>
Persistence & Degradability:	<ul style="list-style-type: none"><li>• The product is expected to be biodegradable</li></ul>
Environmental Hazards:	<ul style="list-style-type: none"><li>• Non-environmentally hazardous</li></ul>
Pack size:	<ul style="list-style-type: none"><li>• 20 Liter and 5 Liter</li></ul>
Shipping Weight:	<ul style="list-style-type: none"><li>• 24.5 Kg</li></ul>
Storage:	<ul style="list-style-type: none"><li>• 9 Months maximum at 25°C (Once opened use within 1 month)</li><li>• Store in cool dry conditions</li></ul>

### **DISCLAIMER**

This data sheet is issued as a guide for use of the product(s) concerned. Whilst SealPro endeavors to ensure that any advice, recommendation, specification or information is accurate and correct, the company cannot – (as SealPro has no direct or continuous control over where and how SealPro products are applied) – accept any liability either directly or indirectly arising from the use of SealPro products, whether or not in accordance with any advice, specification, recommendation or information given by the company. Where other products are to be used in conjunction with this material, the relevant technical data sheets should be consulted to determine total requirements. SealPro has a wealth of technical and practical experience built up over years in the company's pursuit of excellence in building and construction technology.

### **General Disclaimer**

The material and information in these sheets are provided as a guide and without warranties of any kind, either expressed or implied. All warranties, including but not limited to, implied warranties by a representative and fitness for a particular purpose, are disclaimed. In no event shall the Company, nor any of its subsidiaries or affiliates, be liable to any party for any cost or damages, including any direct, indirect, special, incidental, or consequential damages, arising out of the incorrect choice of product and/or method of application.

### **Intellectual Property**

Except as indicated otherwise, all information, text, graphic images, features or functions contained in these Data sheets are the exclusive property of SealPro and may not be copied or distributed, in whole or in part, without the Company's express written consent. However, you may download or print any Data Sheets from the website for personal, non-commercial use, provided you do not remove any copyright notices.